

# *Painter's Putty* Wood Filler/Glazing



- Excellent for filling countersunk nailheads.
- Face glaze wood and metal sash.
- Paintable within 30 minutes.
- For use under all types of paints.
- Clean up with water.



**SAVOGRAN**

# Painter's Putty Wood Filler/Glazing



## Description

Savogran Painter's Putty is a water base compound used for filling countersunk nailheads, crevices and cracks in wood surfaces. The product can be used to glaze wood and metal sash. Painter's Putty is specifically designed for use under all types of interior and exterior paints. Painters prefer it for its quick dry time. Cleanup with water is easy.

## Application

Surfaces and air temperature should be above 40°F. Prime unpainted wood. Make sure that surfaces are clean, dry, frost free and free of sandpaper dust. All old flaking paint and dried putty should be thoroughly removed for proper adhesion. Countersink nails at least 3/16", fill and prime. steel sash and other surfaces that rust must be primed with a rust preventing primer. Knead putty in hands and roll to warm for smoother application. Apply to surface with putty knife or spread firmly with fingers. Painter's Putty can be painted in 30 minutes (with proper conditions) with water base or conventional oil based paints. Cleanup with water.

## Typical Properties

Consistency: Knife grade mastic

Non-volatile: 85%

Binder: Acrylic Latex

Color: White

Weight per gallon: 16 lbs.

Surface Dry: 30 minutes

Prod Code:	Sizes:	Pkd:	UPC:	Ship Wt.:
12880	1/2 Pint	12/case	0 4954212880 3	13 lbs.
12882	Quart	6/case	0 4954212882 7	26 lbs.

Consumer Hotline:  
**800-225-9872**

**The Savogran Company**

P.O. Box 130, Norwood, MA 02062  
Email: [info@savogran.com](mailto:info@savogran.com)

1-800-225-9872 Fax: 781-762-1095  
[www.savogran.com](http://www.savogran.com)

**SAVOGRAN**