

S.I. No. 13 Coating Remover

PRODUCT DESCRIPTION

This product is a liquid, non-methylene chloride coating remover formulated for dip tank or flow-on use. Formulated for stripping shellac, lacquer, varnish and conventional paints. S.I. No. 13 will not darken fine woods.

OUTSTANDING FEATURES

- Contains no methylene chloride.
- Especially good at removing clear finishes and conventional paints.
- Safe to use on all types of wood and metal.
- Minimum drag-out.
- Stripped pieces can be rinsed with water.
- Low evaporation.

CHEMICAL CHARACTERISTICS

Base: Mixed solvent blend
Appearance: Clear liquid
Odor: Aromatic
VOC: 7.02 lbs./gal.
Flash Point: 24°F (T.C.C.)
Viscosity: 10-15 Seconds/#4 Ford Cup
WPG: 7.16 lbs.
pH (1% in H₂O): 6-7

USE INSTRUCTIONS

This product may be used in immersion process tanks or with a flow on system. The exact time for a particular coating can be determined by testing. Stripped surface should be cleaned with a good cleaner to remove all remover residue.

Savogran offers a customer service lab that will determine optimum immersion time and appropriate cleaning agent upon request.

SAFETY PRECAUTIONS: DANGER: FLAMMABLE. Keep away from sparks, heat and flames.
If exhaust fans and/or pumps are used, the motors must be explosion proof. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapors. See material safety data sheet for more complete information.

“MANUFACTURER OF SPECIALTY CHEMICAL COMPOUNDS”

P.O. BOX 130, Norwood, MA 02062-0130

Tel. 800-225-9872 Fax. 781-762-1095