

Xylol is a relatively slow evaporating solvent and thinner for some synthetic coatings as well as paints and varnishes. Has stronger solvent power than mineral spirits. Evaporates slower than Toluol. Should only be used as a thinner when specified by coatings manufacturer. For professional and industrial use only.



Physical Properties

Specific Gravity: 0.873

Weight per Gallon: 7.25 lbs

Boiling Point: 280°F

Flash Point (T.C.C.): 81°F

Vapor Pressure, mm Hg: 7

Evaporation Rate (n-Butyl Acetate=1): 0.86

Important label information

DANGER! HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. Before use, always read all information and warnings on container. Material Safety Data Sheets available upon request.

**KEEP OUT OF REACH OF CHILDREN
CLOSE CONTAINER AFTER EACH USE**

| Prod Code: | Sizes: | Pkd: | UPC: | Ship Wt: |
|------------|---------|--------|-----------------|----------|
| 406001 | Gallon | 4/case | 0 82069 79601 8 | 33 lbs. |
| 406006 | 5 Gal. | Drum | 0 82069 79606 3 | 39 lbs. |
| 406054 | 54 Gal. | Drum | 0 82069 79654 4 | 435 lbs. |