

S.I. No. 5 Coating Remover

PRODUCT DESCRIPTION

This product is a heavy-bodied, water rinsable, non-phenolic paint remover for general purpose applications. Formulated for fast stripping of heavy accumulations of finishes from wood, metal or masonry. Particularly effective for removing alkyds, polyurethane, and varnish.

OUTSTANDING FEATURES

- Nonflammable.
- Especially good at removing heavy accumulations of old paint.
- Safe to use on all types of wood, metal and masonry surfaces.
- Clings to vertical, curved and angular surfaces.
- Stripped pieces can be rinsed with water.
- Safe for veneers and fine wood.

CHEMICAL CHARACTERISTICS

Base: Methylene Chloride, Methanol
Appearance: Thickened liquid
Odor: Mild
VOC: 105 g/l (excluding exempt Methylene Chloride)
Flash Point: None
Viscosity: 40-50 Seconds/#4 Ford Cup
WPG: 10.42 lbs.
pH (1% in H₂O): 6-7

USE INSTRUCTIONS

Brush product on surface to be stripped with a natural bristle paint brush. Use a heavy, even coat with a loaded brush stroking in one direction only. Leave the remover surface undisturbed until the old finish is completely lifted or softened as determined by a scrape test. Allow approximately twenty minutes for coating to be loosened. The exact time for a particular coating can be determined by testing. When the old finish is completely softened remove the sludge with a scraper or coarse rags. Stripped surface should be cleaned with a good cleaner to remove all remover residue.

Savogran offers a customer service lab that will determine optimum dwell time and appropriate cleaning agent upon request.

SAFETY PRECAUTIONS: Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapors. See material safety data sheet for more complete information.

“MANUFACTURER OF SPECIALTY CHEMICAL COMPOUNDS”

P.O. BOX 130, Norwood, MA 02062-0130

Tel. 800-225-9872 Fax. 781-762-1095